



DATA SHEET

Uncompromised Endurance. Unparalleled Performance.

IronWolf Pro 125 SSD



NAS-optimised Seagate® IronWolf® Pro 125 SSDs — offering blistering performance, power loss data protection, and multi-user workload support capable of 1 DWPD.



Best-Fit Applications

- Ultra high endurance NAS
- All-flash array and desktop NAS
- Creative pro, SMB, and SME
- Media server
- SSD cache in enabled NAS

Key Advantages

High Endurance: 1 DWPD delivers endurance and performance, offering the ideal SSD solution for 24x7, multi-user NAS environments

Power Loss Data Protection: Enjoy peace of mind during a power loss knowing your data can stay safe

IronWolf Health Management: Embedded software monitors your SSD NAS drive health in compatible NAS, notifying you to intervene before a catastrophic event occurs

Data Recovery: Rest easy with three years of Seagate Rescue Data Recovery Services, offering an industry-leading 90% success rate against unexpected data loss from power outages, natural disasters, user error, viruses and more

Wide Range of Capacity Options: Choose from an extensive portfolio of capacities, including 240 GB, 480 GB, 960 GB, 1.92 TB, and 3.84 TB

Warranty: Enjoy long-term peace of mind with the included five-year limited warranty protection plan and three-year Rescue Data Recovery Services plan



Specifications					
Capacity	3.84 TB	1.92 TB	960 GB	480 GB	240 GB
Standard Model	ZA3840NX10001	ZA1920NX10001	ZA960NX10001	ZA480NX10001	ZA240NX10001
Features					
Interface	SATA 6 Gb/s	SATA 6 Gb/s	SATA 6 Gb/s	SATA 6 Gb/s	SATA 6 Gb/s
NAND Flash Type	3D TLC	3D TLC	3D TLC	3D TLC	3D TLC
Form Factor	2.5 in x 7 mm	2.5 in x 7 mm	2.5 in x 7 mm	2.5 in x 7 mm	2.5 in x 7 mm
Performance					
Sequential Read (MB/s) Sustained, 128 KB QD32 ¹	545	545	545	545	545
Sequential Write (MB/s) Sustained, 128 KB QD32 ¹	520	520	520	500	360
Random Read (IOPS) Sustained, 4 KB QD32 ¹	96,000	96,000	96,000	96,000	90,000
Random Write (IOPS) Sustained, 4 KB QD32 ¹	30,000	30,000	25,000	16,000	12,000
Endurance/Reliability					
Total Bytes Written (TB)	7,000	3,500	1,750	875	435
Non-recoverable Read Errors per Bits Read	1 per 10E17	1 per 10E17	1 per 10E17	1 per 10E17	1 per 10E17
Mean Time Between Failures (MTBF, hours)	2,000,000	2,000,000	2,000,000	2,000,000	2,000,000
Warranty, Limited (years)	5	5	5	5	5
Power Management					
Power Supply	5V	5V	5V	5V	5V
+5V Active Max Average Power (W)	5.0	4.4	4.0	3.0	2.5
Max Average Idle Power (W)	1.9	1.8	1.6	1.4	1.4
Environmental					
Temperature, Operating Internal (°C)	0 to 70	0 to 70	0 to 70	0 to 70	0 to 70
Temperature, Non- operating (°C)	-40 to 85	-40 to 85	-40 to 85	-40 to 85	-40 to 85
Shock, Non-operating: 0.5 ms (Gs)	1,500	1,500	1,500	1,500	1,500
Physical					
Height (in/mm, max)	0.27 9in/7.10 mm	0.279 in/7.10 mm	0.279 in/7.10 mm	0.279 in/7.10 mm	0.279 in/7.10 mm
Width (in/mm, max)	2.760 in/70.10 mm	2.760 in/70.10 mm	2.760 in/70.10 mm	2.760 in/70.10 mm	2.760 in/70.10 mm
Depth (in/mm, max)	3.950 in/100.35 mm	3.950 in/100.35 mm	3.950 in/100.35 mm	3.950 in/100.35 mm	3.950 in/100.35 mm
Weight (lb/g)	0.136 lb/62g	0.132 lb/60g	0.130 lb/59g	0.123 lb/56g	0.121 lb/55g

¹ Performance data is based on testing under certain workload conditions and is subject to change.



Ordering Information	
Specifications	
Retail Packaging	Box Dimensions
Depth/Length (in/mm)	0.944 in/24 mm
Width (in/mm)	4.291 in/109 mm
Height (in/mm)	6.102 in/155 mm
Weight (lb/kg),	0.37 lb/0.17 kg
Master Carton Dimensions	
Depth/Length (in/mm)	6.023 in/153 mm
Width (in/mm)	11.496 in/292 mm
Height (in/mm)	5.511 in/140 mm
Weight (lb/kg),	4.18 lb/1.9 kg
Pallet Dimensions	
Depth/Length (in/mm)	48.03 in/1,220 mm
Width (in/mm)	40.15 in/1,020 mm
Height (in/mm)	55.90 in/1,420mm
Weight (lb/kg),	956.80 lb/434 kg
Quantities	
Boxes per Master Carton	10
Master Cartons per Pallet	216
Pallet Layers	9

System Requirements	What's Included
---------------------	-----------------

- SATA 6 Gb/s or SATA 3 Gb/s port
- Windows® 10, Windows 8.1
- Linux
- Seagate® IronWolf® Pro 125 SSD

Region	Model Number	Capacity	Limited Warranty (years)	UPC Code	EAN Code	Multi-Pack UPC
WW	ZA3840NX1A001	3.84TB	5	763649146989	8719706027250	10763649146986
WW	ZA1920NX1A001	1.92TB	5	763649146972	8719706027243	10763649146979
WW	ZA960NX1A001	960GB	5	763649146965	8719706027236	10763649146962
WW	ZA480NX1A001	480GB	5	763649146958	8719706027229	10763649146955
WW	ZA240NX1A001	240GB	5	763649146941	8719706027212	10763649146948

seagate.com



© 2020 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. IronWolf and the IronWolf logo are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors, such as chosen interface and disk capacity. Seagate reserves the right to change, without notice, product offerings or specifications. DS2053.1-2007GB July 2020